

Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A navigation apparatus for transmitting information of a guiding route to a navigation terminal for performing route guidance of a moving object, ~~characterized by including~~ comprising:

a communication means for performing unit configured to perform communication with the navigation terminal;

a map data storing means for storing unit configured to store map data;

a route searching means for searching; unit configured to search, using the map data, a guiding route between a departure place and a destination received from the navigation terminal through the communication unit means;

a shape-simplified road map data generating means for generating unit configured to generate, using the map data, shape-simplified road map data which includes at least the guiding route and a road intersecting the recommended route, ~~and in which a road shape of the guiding route is simplified~~ wherein the shape-simplified road map data generating unit linearizes the guiding route including a link and corrects a position of an end of the link or another line connected to an end so that the link straightly-advances or orthogonally intersects another line to simplify a road shape of the guiding route;

a notice part detecting ~~means for detecting~~ unit configured to detect as a notice part a part of the guiding route having a difference greater than a predetermined quantity in angle between a shape of the guiding route in the map data and the shape of the guiding route in the shape-simplified road map data;

a guidance notice information generating ~~means for generating~~ unit configured to generate, on the basis of the difference at the notice part between the map data and the shape-simplified road map data, guidance notice information to be supplied to the navigation terminal when the moving object reaches the notice part in the route guidance; and

an information delivering ~~means for transmitting~~ unit configured to deliver delivery information including the shape-simplified road map data and the guidance notice information to the navigation terminal using the communication ~~means~~ unit.

wherein the guidance notice information generating unit generates the guidance notice information for each of coordinate values included in the notice part and a plurality of coordinate values following the coordinates out of the coordinate values forming the coordinate value string of the guiding route in the road map data on the basis of increase and decrease trends in an angle made between a first line section having a start point or an end point at the coordinate values and a second line section of the guiding route in the shape-simplified road map data, corresponding to the first line section.

2. (Currently Amended) A navigation apparatus for performing route guidance of a moving object, comprising ~~characterized by including~~:

a map data storing means ~~for storing~~ unit configured to store map data;

a setting means ~~for receiving~~ unit configured to receive, settings of a departure place and a destination;

a route searching unit configured to search ~~means for searching~~, using the map data, a guiding route between the departure place and the destination;

a shape-simplified road map data generating means ~~for generating~~ unit configured to generate, using the map data, shape-simplified road map data which includes at least the guiding route and a road, intersecting the recommended route ~~and in which a road shape of the guiding route is simplified~~, wherein the shape-simplified road map data generating unit linearizes the guiding route including a link and corrects a position of an end of the link or another line connected to an end so that the link straightly-advances or orthogonally intersects another line to simplify a road shape of the guiding route;

a notice part detecting means ~~for detecting~~ unit configured to detect as a notice part a part of the guiding route having a difference greater than a predetermined quantity in angle between a shape of the guiding route in the map data and the shape of the guiding route in the shape-simplified road map data; and

a guidance notice information generating ~~means for generating~~ unit configured to generate, on the basis of the difference at the notice part between the map data and the shape-simplified road map data, guidance notice information to be supplied to the navigation terminal when the moving object reaches the notice part in the route guidance,

wherein the guidance notice information generating unit generates the guidance notice information for each of coordinate values included in the notice part and a plurality of coordinate values following the coordinates out of the coordinate values forming the coordinate value string of the guiding route in the road map data on the basis of increase and decrease trends in an angle made between a first line section having a start point or an end point at the coordinate values and a second line section of the guiding route in the shape-simplified road map data, corresponding to the first line section.

3. (Currently Amended) The navigation apparatus as claimed in claim 1, ~~characterized in that~~ wherein the shape-simplified road map data generating ~~means~~ unit performs a process of thinning coordinate values from a coordinate value string forming the guiding route.

4. (Currently Amended) The navigation apparatus as claimed in claim 1, ~~characterized in that~~ wherein the shape-simplified road map data generating

~~means unit~~ performs a process of moving the coordinate values at a connection part between the guiding route and the road intersecting the guiding route.

5. (Currently Amended) The navigation apparatus as claimed in claim 1, ~~characterized in that~~ wherein the shape-simplified road map data generating ~~means unit~~ performs a process of rotating a map forming object of the shape-simplified road map with respect to the departure place of the guiding route.

6. (Currently Amended) The navigation apparatus as claimed in claim 1, ~~characterized in that~~ wherein the notice part detecting ~~means unit~~ detects, with respect to the coordinate values forming the coordinate value string of the guiding route in the road map data, the coordinate values as the notice part when an angle made between a first line section, forming the guiding route, having a start point or an end point at the coordinate values and a second line section of the guiding route in the shape-simplified road map data, corresponding to the first section is equal to or greater than a predetermined value.

Claim 7 (Cancelled).

8. (Currently Amended) A route guiding method in which information of a guiding route is transmitted by a navigation apparatus to a navigation

terminal for performing route guidance of a moving object, ~~characterized by~~
~~including~~ comprising:

a route searching step of searching, using map data stored in a map data storing means unit, a guiding route between a departure place and a destination received from the navigation terminal;

a shape-simplified road map data generating step of generating, using the map data, shape-simplified road map data which includes at least the guiding route and a road intersecting the guiding route and in which a road shape of the guiding route is simplified, wherein the guiding route including a link is linearized and a position of an end of the link or another line connected to an end is corrected so that the link straightly-advances or orthogonally intersects another line to simplify a road shape of the guiding route;

a notice part detecting step of detecting as a notice part a part of the guiding route having a difference greater than a predetermined quantity between a shape of the guiding route in the map data and the shape of the guiding route in the shape-simplified road map data;

a guidance notice information generating step of generating, on the basis of the difference in the notice part between the map data and the shape-simplified road map data, guidance notice information to be supplied to the navigation terminal when the moving object reaches the notice part in the route guidance; and

an information delivering step of transmitting delivery information including the shape-simplified road map data and the guidance notice information to the navigation terminal,

wherein the guidance notice information is generated for each of coordinate values included in the notice part and a plurality of coordinate values following the coordinates out of the coordinate values forming the coordinate value string of the guiding route in the road map data on the basis of increase and decrease trends in an angle made between a first line section having a start point or an end point at the coordinate values and a second line section of the guiding route in the shape-simplified road map data, corresponding to the first line section.

9. (Currently Amended) A route guiding method in which a navigation apparatus performs route guidance of a moving object, characterized by comprising:

a setting step of receiving settings of a departure place and a destination;

a route searching step of searching, using the map data stored in a map data storing ~~means~~ unit, a guiding route between the departure place and the destination;

a shape-simplified road map data generating step of generating, using the map data, shape-simplified road map data which includes at least the guiding route and a road intersecting the guiding route and in which a road shape of the

guiding route is simplified, wherein the guiding route including a link is linearized and a position of an end of the link or another line connected to an end is corrected so that the link straightly-advances or orthogonally intersects another line to simplify a road shape of the guiding route;

a notice part detecting step of detecting as a notice part a part of the guiding route having a difference greater than a predetermined quantity between a shape of the guiding route in the map data and the shape of the guiding route in the shape-simplified road map data; and

a guidance notice information generating step of generating, on the basis of the difference at the notice part between the map data and the shape-simplified road map data, guidance notice information to be outputted when the moving object reaches the notice part in the route guidance,

wherein the guidance notice information is generated for each of coordinate values included in the notice part and a plurality of coordinate values following the coordinates out of the coordinate values forming the coordinate value string of the guiding route in the road map data on the basis of increase and decrease trends in an angle made between a first line section having a start point or an end point at the coordinate values and a second line section of the guiding route in the shape-simplified road map data, corresponding to the first line section.